

## 4.16 Ordering code SJ BS Series Mod.B

SJ	50	BS 40 × 10	Mod.B	RL	Vers. 3 (80 B5)	U-RH	X	FF
1	2	3	4	5	6	7	8	9
C300	IT 5	SFN-D.40.10.5R (Pos.A) + SBC			N	B2	B1	
10	11	12			13			
...								
14								
...								
15								
AC	3-phase	brake motor	0.75 kW	4-pole	230/400 V	50 Hz	IP 55	Ins. F
16								

1	SJ (screw jack SJ BS Series)	
2	Screw jack size	
5 ... 300		page 68 - 69
3	Ball screw	
BS diameter × lead		page 70 - 71
4	Mod.B (Model: travelling nut)	
5	Worm gear ratio	page 68 - 69
6	Input version	
Vers.1, Vers.2, Vers.3, Vers.4, Vers.5, Vers.6		page 8
7	Screw jack mounting and input shaft position	
U-RH, U-LH, D-RH, D-LH, H-RH, H-LH		page 9
8	Fixing plane	
X, Y		page 9
9	Gear box fixing holes	
FF, FP		page 109
10	Screw jack stroke length (example: C300 = 300 mm stroke)	
11	Ball screw accuracy grade	
IT 3 or 5: whirled ball screw		page 70
IT 7: rolled ball screw		page 71
12	Ball nut	
Nut code		page 72 - 75
Pos.A, Pos.B	Orientation of nut mounted on screw	page 113
SBC	Safety nut	page 106
13	Accessories	
N	Screw end	page 96 - 99
B <sub>1</sub> , B <sub>2</sub>	Bellows	page 105
SC	Trunnion mount	page 109
	Worm wheel rotation detector	page 106
14	Other accessories	
example: encoder (with all relevant data)		page 107
15	Other specifications	
example: lubricant for low temperature		
16	Motor data	
17	Product configuration sheet	page 113
18	Application layout	

Product configuration sheet

